



Construction

EXTENSION CORD:

The cable contains high conductivity bunched copper conductors, insulated and colour coded with general purpose flexible grade PVC. The plug is then moulded onto the cable and is constructed of the same cable grade flexible PVC.

Applications

For extension purposes to supply power to all types of electrical, domestic and industrial appliances and equipment. The extension cord sheath is constructed with flame retardant, water and oil resistant flexible grade PVC.

Specification

CORD SETS AND EXTENSION CORD SETS - SABS 1661

Voltage Rating Input voltage 250 Volts

Sheath Colours Black & White

PLUGS AND SOCKET OUTLET - SABS 164.1

Voltage Rating 16A 250V

Sheath Colours Black & White

Packaging

10 amp (1.0mm²) units are available in 10m 20m

16 amp (1.5mm²) units are available in 20m and 30m

20 amp (2.5mm²) units are available in 20m/30m and 40m

* AMP Rating based on Cable Capacity

TECHNICAL DATA

PRODUCT CODE	Size mm ²	Nominal Dia	*Nominal Amps
MP10AMPX3#JC	1.0	7.0	10
MP16AMPX3#JC	1.5	8.2	16
MP20AMPX3#JC	2.5	9.9	20

When ordering, insert colour code here (Refer to Page 1)